

Issue Date July 20, 2024

HELIUM SAFETY DATA SHEET

1.IDENTIFICATION

Product Identifier

Product Name HELIUM

Other means of identification

Safety data sheet number AR 1046 UN/ID no. UN 1046

Trade name HIGH PURITY HELIUM BALLOON GAS

Recommended use of the chemical and restrictions on use

Recommended Use Industrial and professional use. Calibration/test gas.

Uses advised against Precision Equipment Testing

Details of the supplier of the safety data sheet

Surprize Enterprize Inc. 6592 Davand Drive Mississauga Ontario

L5T2M3

Tell: 905-795-1050

For additional product information contact your local customer service.

FOR EMERGENCIES INVOLVING DANGEROUS GOODS Call CANUTEC's 24-hr (ERAP) Number 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Gases Under Pressure	Compressed Gas
Simple Asphyxiants	Yes

Label elements



Signal word Warning

Hazard Statements

Contains gas under pressure; may explode if heated May displace oxygen and cause rapid suffocation

Precautionary Statements • Prevention

Do not handle until all safety precautions have been read and understood Use and store only outdoors or in a well-ventilated place Use a backflow preventive device in piping Use only with equipment rated for cylinder pressure Close valve after each use and when empty

Precautionary Statements • Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention/advice.

Precautionary Statements • Storage

Protect from sunlight when ambient temperature exceeds 52°C/125°F

Hazards not otherwise classified (HNOC)

Not applicable

Intentional inhalation of helium balloon gas can cause asphyxiation, lung damage, and death.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure Gas

Chemical	CAS No.	Volume %	Chemical Formula	
Helium	7440-59-7	>99	He	

4. FIRST AID MEASURES

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation move to fresh air and keep comfortable for breathing. If breathing is difficult, give

oxygen. If breathing has stopped, give artificial respiration. Get medical attention

immediately.

Skin contact None under normal use. Get medical attention if symptoms occur.

Eye contact Not an expected route of exposure

Ingestion None under normal use. Get medical attention if symptoms occur.

Self-protection of the first

aider

RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED

BREATHING APPARATUS.

Most important symptoms and effects, both acute and delayed

Symptoms Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to

oxygen-deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen

may cause serious injury or death.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media None.

Specific extinguishing methods

Continue to cool fire exposed cylinders until flames are extinguished. Damaged cylinders should be handled only by specialists.

Specific hazards arising from the chemical

Non-flammable gas. Cylinders may rupture under extreme heat.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions. protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined

areas. Monitor oxygen level. Wear self-contained breathing apparatus when entering

area unless atmosphere is proved to be safe.

Environmental precautions

Environmental precautions Prevent spreading of vapors through sewers, ventilation systems and confined are.

Methods and material for containment and cleaning up

Methods for containment Stop the flow of gas or remove cylinder to outdoor location if this can be done without

risk. If a leak is in the container or container valve, contact the appropriate emergency

telephone number in Section 1 or contact our office.

Methods for cleaning up Return cylinder to Surprize Enterprize Inc. / Airise Gases.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Proper handling, storage of regulating equipment and cylinders is required to safely fill helium balloons. DO NOT ALLOW CHILDREN OR UNQUALIFIED PEOPLE TO OPERATE BALLOON-FILLING EQUIPMENT. INTENTIONAL INHALATION OF HELIUM CAN CAUSE SERIOUS LUNG DAMAGE OR DEATH. A balloon filling helium regulator must be attached to the valve before it is opened.

Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distance, use a cart designed to transport cylinders. Never attempt to lift a cylinder by gripping its valve protection cap. Never insert an object (e.g. wrench, screwdriver, pry-bar,etc.) into valve cap openings. Doing so may damage valves, causing a leak to occur. Use an adjustable strap wrench to remove over-tight or rusted caps. Use only with adequate ventilation. Use a backflow preventive device in piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Ensure the complete gas system is checked for leaks before use.

Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never attempt to refill a compressed gas cylinder without the owner's written consent. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.

Only experienced and properly instructed people should handle gases under pressure. Always store and handle compressed gas cylinders in accordance with Compressed Gas Association, publication CGA-P1, Safe Handling of Compressed Gases in Containers.

Conditions for safe storage including any incompatibilities

Storage Conditions Store in cool, dry, well-ventilated area of non-combustible construction away from heavily

trafficked areas and emergency exits. Keep at temperatures below 52oC /125°F. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Full and empty cylinders should be segregated. Stored containers

should be periodically checked for general condition and leakage.

Incompatible materials None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HELIUM 7440-59-7	See Appendix F: Minimal Oxygen Content	None	None

ACGIH TLV: American Conference of Governmental industrial Hyg1emsts - Threshold Llm1t Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Provide general ventilation, local exhaust ventilation, process enclosure or other

engineering controls to maintain airborne levels below recommended exposure limits and to maintain oxygen levels above 19.5%. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly

checked for leakages.

Individual protection measures. such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Work gloves and safety shoes are recommended when handling cylinders.

Respiratory protection Use positive pressure airline respirator with escape cylinder or self-contained

breathing apparatus for oxygen-deficient atmospheres (<19.5%).

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Gas Colorless Appearance Odor Odorless Odor threshold pH Not applicable Melting/freezing point Not applicable Boiling point / boiling range Not applicable Evaporation rate -268.9 ·c r -452.1 ·F Flammability (solid, gas) Not applicable Lower flammability limit: Non-flammable gas Upper flammability limit: Not applicable Not applicable Flash point Autoignition temperature Not applicable Decomposition No data available temperature No data available Water solubility Slightly soluble Partition coefficient No data available Kinematic viscosity Not applicable

Component Level Information:

Chemical Name	Molecular	Boiling	Vapor	Vapor density	Gas Density	Critical
	weight	point/range	Pressure	·(air =1)	kgfm3@2o•c	Temperature
HELIUM	4.00	-268.9 ·c	Above critical temperature	0.138	0.165	-267.9 ·c

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions

Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

None under recommended storage and handling conditions (see Section 7).

Incompatible materials

None known.

Hazardous Decomposition Products

None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Product is a simple asphyxiant.

Skin contact No data available

Eye contact No data available

Ingestion Not an expected route of exposure

Information on toxicological effects

Symptoms

Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<=19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Not classified
Sensitization Not classified
Germ cell mutagenicity Not classified

Carcinogenicity This product does not contain any carcinogens or potential carcinogens listed by OSHA,

IARC or NTP

Reproductive toxicity Developmental Toxicity STOT- single exposure STOT- repeated exposure

Chronic toxicity Not classified Aspiration hazard Not classified

Numerical measures of toxicity

Product Information

Oral LD50 No information available
Dermal LD50 No information available
Inhalation LC50 No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

No known acute aquatic toxicity.

Persistence and degradability

No information available.

Bioaccumulation

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Treatment methods

Disposal of waste: Do not attempt to dispose of residual waste or unused quantities. Return in the shipping

container PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to SURPRIZE ENTERPRIZE INC./AIRISE

GASES INC. for proper disposal.

14. TRANSPORT INFORMATION

<u>DOT</u>

UN/ID no. UN1046

Proper shipping name Helium, compressed

Hazard Class 2.2

Description UN1046, Helium, compressed, 2.2

Emergency Response Guide Number 121

TDG

UNIID no. UN1046

Proper shipping name Helium, compressed

Hazard Class 2.2

Description UN1046, Helium, compressed, 2.2

IATA

UNIID no. UN1046

Proper shipping name Helium, compressed

Hazard Class 2.2 ERG Code 2L Special Provisions A69

Description UN1046, Helium, compressed, 2.2

IMDG

UNIID no. UN1046

Proper shipping name Helium, compressed

Hazard Class 2.2 EmS-No. F-C, S-V

Description UN1046, Helium, compressed, 2.2

15. REGULATORY INFORMATION

INTERNATIONAL INVENTORIES

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies

Legend:

TSCA- United States Toxic Substances Control Act Section 8(b) Inventory

DSUNDSL- Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

US FEDERAL REGULATIONS

SARA313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Clean Air Act. Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Risk and Process Safety Management Programs

This material, as supplied, does not contain any regulated substances with specified thresholds under 40 CFR Part 68. This product does not contain any substances regulated as Highly Hazardous Chemicals pursuant to the 29 CFR Part 1910.110.

US STATE REGULATIONS

California Proposition 65

This product does not contain any Proposition 65 chemicals

16. OTHER INFORMATION

NFPA Health hazards 0 Flammability 0 Instability 0 Physical and Chemical Properties Simple asphyxiant

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2019, CGA Recommended Hazard Ratings for Compressed Gases, 4th Edition.

Issue Date: 20-July-2024

AR-1060

General Disclaimer

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Surprize Enterprize Inc., Airise Gases Inc. (or any of their affiliates and subsidiaries) and the purchaser.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End of Safety Data Sheet